PRO-LOK Why Use Anything Else?

A042 Long Reach Tool

The AO42 is a 3 piece tool held together by 2 connectors. To assemble your tool, thread the rods into the connectors.

To bend the AO42, grasp one connector in each hand and gently bend the long rod section to the desired curve.

The AO42 is intended for use with frameless windows. The AO42 must be used with a wedge. Gently insert the wedge into the upper portion of the rear edge of the passenger window, spreading the window outward approx. 1/4" (see photos 1 & 2.) Protect the edge of the glass by inserting the AO42-SL plastic sleeve between the glass and the door to frame to avoid tool contact with the edge of the glass. Carefully feed the tool through the sleeve.

APPLICATION 1- Retrieve the key by inserting either end of the tool and hooking onto the key ring. Carefully retrieve the keys. You may be able to thread them through the opening, or read the code or cuts on the key.

APPLICATION 2- Activate the power unlock button by inserting either end of the tool and depressing the unlock button on the console or on the opposite door.

APPLICATION 3- Manipulate locking lever with the "L" end of the tool (see photo 3.)

APPLICATION 4- Manipulate the vertical button by inserting the "J" end of the tool and accessing the vertical button on the opposite door. Hook button head and rotate tool clockwise to raise button head.

APPLICATION 5- Access the pull handle. (which opens the door when in the locked position) by inserting the end of the tool and hooking the pull handle on the opposite door. Pull the tool towards you to unlock door.











GENERAL APPLICATIONS: This tool works on some: BMW. CHRYSLER. CHEVROLET. FORD. HONDA. MERCEDES. MERCURY, MITSUBISHI, TOYOTA, VOLVO and various other makes and models.